







Canon's comprehensive portfolio of imageRUNNER ADVANCE multifunction printers and integrated solutions can help **simplify** the end user experience and management of technology, better **control** sensitive information and print-related costs, and help ensure that technology investments proactively **evolve** with changing needs.

Colour | Mid-volume | Multifunction

# CANON

# C5500 / C5560i / C5550i / C5540i / C5535i MAIN SPECIFICATIONS



### Main Unit

Colour Laser Multifunctional

**Core Functions** 

Standard: Print, Copy, Scan, Send, Store Optional Fax

**Processor Speed** 

Canon Dual Custom Processor (Shared)

**Control Panel** 

10.1" TFT LCD WSVGA Colour Flat-panel

Memory 40 GBRAM

Hard Disk

Standard: 250 GB/Maximum: 1 TB

Interface Connection

1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n)

Standard: USB 2.0 x2 (Host), USB 3.0 x1 (Host),

USB 2.0 x1 (Device)

Serial Interface, Copy Control Interface Optional:

Paper Output Capacity (LTR, 20 lb. Bond)

Standard: 250 Sheets Maximum 3 450 Sheets

(with External Finisher and Copy Tray)

Paper Sources (LTR, 20 lb. Bond)

Dual 550-sheet Paper Cassettes. Standard 100-sheet Stack Bypass Dual 550-sheet Paper Cassettes (CASSETTE FEEDING UNIT-AMI), Optional 2,450-sheet High Capacity Paper Cassette (HIGH CAPACITY CASSETTE FEEDING

UNIT-A1), 2,700-sheet Paper Deck (PAPER DECK UNIT-F1)

Paper Capacity (LTR, 20 lb. Bond)

Standard: 1.200 Sheets 6,350 Sheets Maximum:

**Finishing Capabilities** Standard:

Collate, Group, Offset, Staple, Hole Punch, With Inner Staple-free Staple, Staple On Demand Collate, Group, Offset, Staple, Booklet, Hole Finishers Punch, Staple-free Staple, Staple On Demand

Supported Media Types

Thin, Plain, Recycled, Colour, Heavy, Cassette 1

Pre-punched, Letterhead, Bond, Transparency, Envelope

Thin, Plain, Recycled, Colour, Heavy, Pre-punched, Letterhead, Bond, Paper Cassette 2:

Transparency, Tab, Envelope Thin, Plain, Recycled, Colour, Heavy Stack Bypass: Pre-punched, Labels, Letterhead, Bond,

Coated, Transparency, Tab, Tracing,

Supported Media Sizes

Letter, Executive, Statement-R, Envelope [No.10 (COMI0), DL., ISO-CS], Custom Size (3-7/8" x 5-7/8" to 11-3/4" x 8-1/2") 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R, Envelope Cassette 1

Cassette 2: Executive, Statement-R, Envelope (No.10 (COM10), Monarch, DL, ISO-C5], Custom Size (3-7/8" x 7-1/8" to 12" x 18") 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement, Statement-R, Stack Bypass:

Envelope [No.10 (COM10), Monarch, DL ISO-C5), Envelope Custom Size (3-7/8" x 3-7/8" to 12-5/8" x 18"), Custom Size (3-7/8" x 5-1/2" to 12-5/8" x 18"), Free Size (3-7/8" x 5-1/2" to 12-5/8" x 18")

Cassettes 14 lb. Bond to 140 lb. Index (52 to 256 g/m²) 14 lb. Bond to 110 lb. Cover (52 to 300 g/m²) Stack Bypass: 14 lb. Bond to 80 lb. Cover (52 to 220 g/m²)

Warm-up Time

From Power On: Approx. 10 Seconds<sup>4</sup> Approx. 10 Seconds<sup>5</sup> From Sleep Mode: Approx. 4 Seconds<sup>6</sup> Quick Startup Mode:

Dimensions (W x D x H)

24-3/8" x 29-1/4" x 47-2/7" (620 mm x 742 mm x 1201 mm)<sup>7</sup>

Installation Space (W x D)

Stack Bypass + Cassette Drawers open: 37-1/8" x 46-3/8" (943 mm x 1176 mm)<sup>7</sup> Basic:

Approx. 310.9 lb. (141kg)8

**Print Specifications** 

Print Speed (BW and Colour)

C5560i III:

C5550i III

We and Colour)
Up to 60 ppm (Letter); Up to 36 ppm
(Letter-R); Up to 34 ppm (Legal);
Up to 32 ppm (11" x 17")
Up to 50 ppm (Letter); Up to 30 ppm
(Letter-R); Up to 29 ppm (Legal);
Up to 27 ppm (11" x 17")
Up to 40 ppm (Letter); Up to 24 ppm
(Letter); Up to 24 ppm (Letter); U C5540i III:

(Letter-R); Up to 23 ppm (Legal); Up to 22 ppm (11" x 17") C5535i III: Up to 35 ppm (Letter); Up to 23 ppm (Letter-R); Up to 21 ppm (Legal);

Up to 18 ppm (11" x 17") Print Resolution (dpi)

1200 x 1200, 600 x 600

Standard Page Description Languages

UFR II, PCL6, Adobe PS 3

**Direct Print** 

Available from USB, Advanced Box, Remote UI, and Web Access

Supported File Types PDF, TIFF, JPEG, EPS,10 XPS

Printing from Mobile and Cloud-based Services

A range of software and MEAP-based solutions are available to provide printing from compatible mobile devices or Internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for further information.

Fonts

93 Roman. 10 Bitmap fonts, 2 OCR fonts, PCI fonts

Andalé Mono WT J/K/S/T (Japanese, Korean, Simplified and Traditional Chinese), 12 Barcode Fonts 13

PS fonts: 136 Roman

Operating System<sup>14</sup> Windows Server 2008/Windows 7/Server

2008 R2/Server 2012/Windows 8.1/Server 2012 R2/Windows 10/Server 2016, MAC OS

X (10.9 or later) Windows Server 2008/Windows 7/Server PCI

Windows Server 2002/Windows //Server 2008 R2/Server 2012/Windows 8.1/Server 2012 R2/Windows 10/Server 2016 Windows Server 2008/Windows 7/Server 2008 R2/Server 2012/Windows 8.1/Server PS 2012 R2/Windows 10/Server 2016, MAC OS

MAC OS X (10.3.9 or later), Windows 7/8.1/10

Copy Specifications

Copy Speed (BW and Colour)

C5560i III: Up to 60 ppm (Letter);Up to 36 ppm

(Letter-R); Up to 34 ppm (Legal); Up to 32 ppm (11" x 17") C5550i III

Up to 32 ppm (I1 x I7 ) Up to 50 ppm (Letter); Up to 30 ppm (Letter-R); Up to 29 ppm (Legal); Up to 27 ppm (I1" x I7") Up to 40 ppm (Letter); Up to 24 ppm C5540i III:

(Letter-R); Up to 23 ppm (Legal); Up to 22 ppm (11" x 17") Up to 35 ppm (Letter); Up to 23 ppm

C5535i III: (Letter-R); Up to 21 ppm (Legal); Up to 18 ppm (11" x 17") First-Copy-Out Time

C5560i III: As fast as 2.9 seconds (BW)/ 4.5 seconds (Colour)
As fast as 3.5 seconds (BW)/ C5550i III-5.2 seconds (Colour) As fast as 4.1 seconds (BW)/ C5540i III: 6.1 seconds (Colour) As fast as 4.9 seconds (BW)/ C5535i III: 7.4 seconds (Colour)

Copy Resolution (dpi)

600 x 600 Reading: Printing 1200 x 1200

**Multiple Copies** 

Up to 999 Magnification

25%-400% (1% Increments)

**Preset Reductions** 25%, 50%, 64%, 73%, 78%

**Preset Enlargements** 

121%, 129%, 200%, 400%

Basic Copy Features
Preset Reduction/Enlargement Ratios by Area, Paper Setting, Previous Settings, Favorite Settings, Finishing, Two-sided, Density Adjustment, Original Type Selection, Interrupt Mode, Setting Confirmation/Cancel

**Special Copy Features** 

Book to Two Pages, Two-sided Original, Finishing, Booklet, Job Build, N on I, Add Cover, Insert Sheets, Different-size Originals, Density Adjustment, Original Type Selection, Transparency Cover Sheets, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark Print Date, Shift, Gutter, Print & Check, Negative/Positive, Repeat Images, Merge Job Blocks, Job Done Notice, Mirror Image, Print on Tab, Store in Mail Box, Superimpose Image, Copy ID Card, Skip Blank Pages, Detect Feeder Multi Sheet Feed, Free Size Original, Colour Balance, Adjust One-Touch Colour, Area Designation

Scan Specifications

Colour Platen and Single-Pass Duplexing Automatic

**Document Feeder Paper Capacity** 

150 Sheets (20 lb. Bond)

**Document Feeder Supported Media Sizes** 

11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Custom Size: 5" x 5-1/2" to 12" x 17"

**Document Feeder Supported Media Weights** BW Original: 13 lb. Bond to 58 lb. Cover (50 to 157 g/m²) Colour Original: 17 lb. Bond to 58 lb. Cover (64 to 157 g/m²)

Platen Acceptable Originals

Sheet, Book, 3-Dimensional Objects [Height: up to 2" (50 mm), Weight: Up to 4.4 lb. (2kg)]

Colour Network ScanGear2 for both Twain and WIA Supported OS: Windows 7/8.1/10 Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/Server 2016

Scan Resolution (dpi)

 $600 \times 600, 400 \times 400, 300 \times 300, 200 \times 400, 200 \times 200, 200 \times 100, 150 \times 150, 100 \times 100$ 

Scan to Mobile Devices and Cloud-based Services

A range of solutions is available to provide scanning to compatible mobile devices and certain cloud-based services depending on your requirements

Scan Speed (Letter)

Single-sided Scanning

BW: 80 ipm (300 dpi)/80 ipm (600 dpi) 80 ipm (300 dpi)/60 ipm (600 dpi) Colour:

Double-sided Scanning

160 ipm (300 dpi)/150 ipm (600 dpi) 160 ipm (300 dpi)/80 ipm (600 dpi) Colour

# CANON

# C5500 / C5560i / C5550i / C5540i / C5535i MAIN SPECIFICATIONS



# Send Specifications

#### Destination

Email/Internet Fax (SMTP), SMB v3.0, FTP, WebDAV, Mail Box, Super G3 Fax (Optional), IP Fax (Optional)

#### Address Book

LDAP (2,000)/Local (1,600)/Speed Dial (200)

Send Resolution (dpi)  $600\times600,400\times400,300\times300,200\times400,200\times200,200\times100,150\times150,100\times100$ 

### Communication Protocol

FTP (TCP/IP), SMB v3.0, WebDAV

Fmail-SMTP POP3

#### File Format

Standard

TIFF, JPEG, PDF (Encrypted, Compact, Searchable, Apply Policy, Optimize for Web, PDF A/1-b, Limited Colour Device Signature), XPS (Compact, Searchable, Device Signature), Office Open XML (PowerPoint,

PDF (Trace & Smooth, User Signature), Optional:

XPS (User Signature)

### Universal Send Features

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Delayed Send, Preview, Job Done Notice, File Name, Subject/ Message, Reply-to, Email Priority, TX Report, Original Content Orientation, Skip Blank Originals, Detect Feeder Multi Sheet Feed

# Fax Specifications (Optional)

#### Modem Speed

Super G3: 33.6 Kbps

#### Compression Method MH, MR, MMR, JBIG

Resolution (dpi)

400 x 400, 200 x 400, 200 x 200, 200 x 100

# Sending/Recording Size

Statement-R to 11" x 17"

# Fax Memory

Up to 30,000 Pages

# **Speed Dials**

# Group Dials/Destinations

Max. 199 Dials

# Sequential Broadcast

Max. 256 Addresses

## Memory Backup

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density for Scanning, Sharpness, Copy Ratio, Erase Frame, Job Build, Sender's Name (TTI), Select Line, Selecting the Telephone Line, Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Detect Feeder Multi Sheet Feed

# Store Specifications

# Mail Box (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, 30,000 Maximum Pages Stored

#### Advanced Box

Communication Protocol: SMB or WebDAV

Supported

Client PC: Windows (Windows 7/8.1/10)

Concurrent Connections (Max.)

SMB 64

WebDAV: 3 (Active Sessions)

## Advanced Box Available Disc Space

Approx. 16 GB (Standard HDD) Approx. 480 GB (With Optional 1 TB HDD)

#### Advanced Box Features

Authentication for Advanced Box Log-in, Sort Function, Printing a PDF File with a Password

# Memory Media

Standard: USB

# Security Specifications

Universal Login Manager, uniFLOW Online Standard:

Express,15 User Authentication, Department ID Authentication, Access Management System, Device and Function Level Log-in uniFLOW

Optional:

#### Data

Standard

Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption (FIPS140-2 Validated), Verify System at Startup, McAfee Embedded Control<sup>19</sup>
Hard Disk Drive Mirroring, Hard Disk

Drive RSemoval, IEEE 2600.2 Common Criteria Certification, Data Loss Prevention

(Requires uniFLOW)

#### Network Standard

Optional:

Encrypted Secure Print, IP/Mac Address Filtering, IPsec, TLS Encrypted Communication, SNMP V3.0, IEEE 802.IX, IPv6, SMTP Authentication, POP Authentication before SMTP, S/MIME, SIEM Integration

Document

Standard

Secure Watermark, Secure Print, Adobe LiveCycle® Rights Management ES2.5 Integration, Encrypted PDF, Encrypted

Optional:

Secure Print, Digital Signature User Signature, Document Scan Lock

# **Environmental Specifications**

# **Operating Environment**

Temperature: 50 to 86° F

20 to 80% RH (Relative Humidity) Humidity:

#### **Power Requirements**

C5560iIII/

C5550i III: 120-127V AC 60 Hz,11.5 A C5540i III/

120-127V AC.60 Hz.10 A C5535i III:

## Plug (Main Unit)

C5560i III/

**NFMA 5-20P NFMA 5-15P** C5535iIII-

### Power Consumption

Maximum: Approx. 1,800 W Standby Approx. 65.2 W Sleep Mode: Approx. 0.8 W

Typical Electricity Consumption (TEC) Rating 0.86 kWh (iR ADV C5560i III)

0.70 kWh (iR ADV C5550i III) 0.58 kWh (iR ADV C5540i III) 0.46 kWh (iR ADV C5535i III)

#### Standards

ENERGY STAR ® Certified

# Consumables

#### Toner

GPR-55 Toner<sup>18</sup>

# Toner Yield (Estimated @ 5% Coverage)

Black: 69,000 Images Colour (C,M,Y): 60,000 Images

- Subscription to a third-party cloud service required. Subject to third-party cloud service providers' terms and conditions.

- Teleplace pairs use its earlier between the same conditions.

  The same types of tracing paper cannot be used.

  Time from device power-on to when copy jobs can be programmed with Quick Start Up mode.

  Time from exiting Sleep mode to when printing is operational.

  Time from device power-on to when key operation can be performed on the touch screen.

- Includes main unit and either Cassette Feeding Unit-AMI, High Capacity Cassette Feeding Unit-AI, or Cabinet Type-N. Includes main unit, consumables, and Cassette Feeding Unit-AMI.
- PDF print from Web sites is supported.
   EPS can be printed directly only from the Remote User Interface
- <sup>11</sup>For more information, including compatibility, please visit
- 12 Requires the optional PCL International Font Set-Al 13 Requires the optional Barcode Printer Kit-Dl.
- \*Netguines the optional bar code Printer NI-DI.

  \*Other operating systems and environments including AS/400, UNIX, Linux and Citrix may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.
- <sup>15</sup> No charge for this solution; however activation is required <sup>16</sup> Reference Value (measured one unit).
- <sup>17</sup> 0.8 W Sleep mode not available in all circumstances due to certain settings.
- 18 GPR-55L Toner also available for Colour (C, M, Y). Yield (estimated @ 5% coverage) is 26,000 images.
- Requires Unified Firmware Platform v3.9
   Based on ENERGY STAR Product Specification for Imaging Equipment Version 3.0.

For detailed specifications and a comprehensive list of optional accessories, see the imageRUNNER ADVANCE C5500 III Series