

B&W Multi Function Printer

RICOH
IM 2500
IM 3000
IM 3500
IM 4000
IM 5000
IM 6000

☑ Copier ☑ Printer ☑ Facsimile ☑ Scanner

RICOH
imagine. change.



RICOH
IM 2500

25
ppm Monochrome

RICOH
IM 3000

30
ppm Monochrome

RICOH
IM 3500

35
ppm Monochrome

RICOH
IM 4000

40
ppm Monochrome

RICOH
IM 5000

50
ppm Monochrome

RICOH
IM 6000

60
ppm Monochrome

GENERAL

Warm-up time	18- 19.1 Seconds
First Output Speed : B/W	2.3 - 4.1 Seconds
Continuous output speed	25-60 ppm
Memory	2GB standard/maximum
HDD	320GB standard/maximum
Weight (Mainframe)	200kg or less
Dimensions (W x D x H)	Standard: 690 x 883 x 1161mm
Power Source	220-240V, 50-60Hz

COPIER

Multiple copying	Up to 999 copies
Resolution	600 dpi
Zoom	From 25% to 400% in 1% steps

SCANNER

Scanning Speed: ARDF	80 ipm (200/300 dpi)
Scanning Speed: SPDF	Simplex: 120 ipm (200 dpi), 110 ipm (300 dpi)
	Duplex: 240 ipm (200 dpi), 180 ipm (300 dpi)
Resolution	Up to 600 dpi
File Formats	Single Page TIFF (Compression on, Compression off), Single page JPEG, Single page PDF, Single page High Compression PDF, Single page PDF/A, Multi page TIFF, Multi page PDF, Multi page High compression PDF, Multi page PDF/A
Scan modes	E-mail, USB, SD Card, URL, FTP, SMB

PRINTER

CPU	Intel Atom processor ApolloLake-I 1.6GHz
Printer Language	Standard : PCL5e, PCL6, PDF Direct Option : Genuine Adobe PostScript 3, IPDS, PDF Direct from Adobe
Print resolution	Maximum: Up to 1200 x 1200 dpi
Network interface	Standard: Ethernet 1- baseT/100 base-TX 1000 base-T, USB Host I/F Type A, USB Device I/F, Type B Option: Bi-directional IEEE 1284, Wireless LAN (IEEE 802.11a/b/g/n) Additional NIC (2nd Port)
Mobile printing capability	Apple AirPrint, Mopria, NFC, RICOH Smart Device Connector
Windows environments	Windows 8.1/10, Windows Server 2012/2012R2/2016, Windows Server 2019
Mac OS environments	Macintosh OS X v10.13 or later
UNIX environments	UNIX Sun Solaris, HP-UX, SCO Open Server, RedHat Linux, IBM AIX, Citrix XenApp
SAP environments	7.6 LTSR, 7.15 LTSR, VirtualApps/Desktop 7 1912 and later
Other supported environment	SAP R.3, SAP S/4 NDPS Gateway AS/400 using OS/400 Host Print Transform

FAX

Circuit	PSTN, PBX
Transmission speed	2 seconds
Modem speed	33.6 Kbps maximum
Resolution	Standard mode: 8 x 3.85 line/mm, 200 x 100 dpi, 8 x 7.7 line/mm. 200 x 200 dpi option: 16 x 15.4 line/mm, 400 x 400 dpi
Compression method	MH, MR, MMR JBIG
Memory	Standard: 4MB, Maximum: 60MB

ECOLOGY

Power consumption: Maximum	1600W -1780W or less
Power consumption: Operation	446W - 821W
Power consumption: Ready	56.4W - 64.72W
Power consumption: Sleep mode	0.57W
TEC	0.29 - 0.74 kWh

PAPER HANDLING

Recommended paper size	A3, A4, A5, B, B5, B6
Paper input capacity	Standard: 4300 sheets (inc bypass 100 sheets) Maximum: 8700 sheets (inc bypass 100 sheets)
Paper output capacity	Standard: 500 sheets Maximum: 3500 sheets
Paper weight	Standard Tray-60-300g/m2, Bypass:52-300 g/m2 Duplex: 52-256 g/m2
Paper Types	Plain paper, Recycle Paper Colour 1-2, Special Paper, Color paper, cardstock, preprinted paper, coated paper, Letterhead, Bond Paper, Trace Paper Envelope, Label paper, OHP

THINK COPIER CALL V COPIER**03 4280 2285 | 012 719 2285 | 017 627 2285****www.vcopier.com.my**