

Full Colour Multi Function Printer

IM C2010

IM C2510

IM C3010

IM C3510

IM C4510

IM C6010

☒ Printer ☒ Copier ☒ Scanner ☒ Fax



IM C2010



20 ppm

IM C2510



25 ppm

IM C3010



30 ppm

IM C3510



35 ppm

IM C4510



45 ppm

IM C6010



60 ppm

GENERAL

Functions	Copy, Print, Scan, Fax
Operation Panel	10.1" Smart Operation Panel
Warm-up time	20 Seconds
First Output Speed : B/W	3.2 Seconds
Continuous output speed	70 ppm
CPU	Intel Apollo Lake Processor 1.6 GHz
Memory	2GB standard/maximum
HDD	320GB standard/maximum
Weight (Mainframe)	200kg or less
Dimensions (W x D x H)	Standard: 690 x 883 x 1161mm
Power Source	220-240V, 50/60Hz

COPIER

Multiple copying	Up to 999 copies
Resolution	600 X 600 dpi
Zoom	From 25% to 400% in 1% steps

FAX

Circuit	PSTN, PBX
Transmission speed	G3: approximately 2 secs (200 x 100 dpi, JBIG, ITUT #1 chart TTI off, memory transmission) G3: approximately 2 secs (200 x 100 dpi, MMR, ITUT #1 chart TTI off, memory transmission) 33.6 Kbps maximum
Modem speed	Standard mode: 8 x 3.85 line/mm, 200 x 100 dpi
Resolution	Detail mode: 8 x 7.7 line/mm, 200 x 200 dpi Super fine mode: 8 x 15.4 line/mm, 16 x 15.4 line/mm, 400 x 400 dpi (with optional SAF memory)
Compression method	MH, MR, MMR, JBIG
SAF memory size	Standard: 4MB Maximum: 60MB

PRINTER

Printer	Language Standard : PCL5e, PCL6, PostScript, PDF Direct Option : Genuine Adobe PostScript 3", IPDS, PDF Direct from Adobe
Print resolution	Maximum: 1200 x 1200 dpi
Network interface	Standard: Ethernet 10- baseT/100 base-TX/1000 base-T, USB Host Type A, USB Device I/F Type B, Bluetooth, Wireless LAN (IEEE 802.11 b/g/n), USB Host I/F, SD slot, NFC tag, USB Device (Type B:IPort)
Network interface	Option: Bi-directional IEEE 1284, Wireless LAN (IEEE 802.11 a/b/g/n), RJ45 I/F (Only Copy connect), Ethernet Print only RJ-45 network port
Windows environments	Windows 7/8. 1/10, Windows Server 2008/2008R/2012/2012R2/2016, Window server 2019
Mac OS environments	Macintosh OS X v 10.12 or later
UNIX environments	UNIX Sun, Solaris UNIXSun , Solaris, HP-UX, SCO Open Server, RedHat Linux, IBM,XenDesktop,
SAP environments	AIX, Citrix XenApp 7.12 or later, LTSR, Citrix XenVirtualApp/CenDesktop 7 1808 and later SAP R/3, SAP S/4

FAX

Scanning Speed B/W	120 ipm (Simplex)/240ipm(Duplex)
Scanning Speed Full Colour	120 ipm (Simplex)/240ipm(Duplex)
Resolution	600 dpi maximum
Compression method	TIFF (MG, MR, MMR, JBIG2) Grayscale, JPEG (Color)
File Formats	Single Page TIFF, Single page JPEG, Single page PDF, Single page High Compression PDF, Single page PDF/A, Multi page TIFF, Multi page PDF, Multipage High compression PDF, Multipage PDF/A
Scan modes	E-mail, Folder USB, SD Card, URL, FTP, SMB

PAPER HANDLING

Recommended paper size	A3, A4, A5, A6, B4, B5, B6
Paper input capacity	Standard: 4300 sheets Maximum: 8700 sheets
Paper output capacity	Standard: 500 sheets Maximum : 3500 sheets
Paper weight	Standard Trays: 52-256g/m3 Duplex 64 - 256 g/m3
Paper Types	Plain paper, Recycle Paper Color 1-2, Special Paper, Letterhead, Bond Paper, Trace Paper Label paper

PAPER HANDLING

TEC Value	1.454 - 1.87 kWh
Power consumption	Maximum1.9 - 2.1 kWh or less Ready : 254 W Sleep : 0.54-0.55W