

Colour Multifunction Printer

MP C3004(A)SP
MP C3504(A)SP
MP C4504(A)SP
MP C5504(A)SP
MP C6004SP

✓ Copier ✓ Printer ✓ Facsimile ✓ Scanner

RICOH
imagine. change.



MP
C3004(A)SP

30
ppm

Colour

MP
C3504(A)SP

35
ppm

Colour

MP
C4504(A)SP

45
ppm

Colour

MP
C5504(A)SP

55
ppm

Colour

MP C6004SP

60
ppm

Colour

MAIN SPECIFICATIONS

GENERAL

Warm-up time	25/24 seconds
First output speed: B/W	4.6/3.1 seconds
First output speed: Full Color	7.1/4.5 seconds
Continuous output speed	37 - 60 ppm
Memory	4GB maximum
HDD	250-320GB
Dimensions (W x D x H)	587 X 685 X 963 mm
Weight	101.3-103.4 kg
Power Source	220-240V, 50/60Hz

ECOLOGY

Power consumption: Maximum	1700W or less
Power consumption: Ready	47.4 - 59W or less
Power consumption: Sleep mode	0.55 - 0.62 W or less
TEC Value	1.1 - 2.7 kWh

PRINTER

Printer Language	Standard : PCL5c, PCL6XL, PDF Option : XPS, Adobe PostScript 3tm, IPDS, PictBridge
Print resolution	Maximum: 1200 x 1200 dpi
Network interface	Standard: SD Slot, USB Host I/F, Ethernet 10 base-T/100 base-TX/1000 base-T
Network interface	Option: Wireless LAN (IEEE 802.11a/b/g/n), Bluetooth, USB Server for Second Network Interface, Bi-directional IEEE 1284/ECP, USB 2.0 (Type B)
Mobile printing capability	Apple AirPrint
Windows environments	Windows 7/8. 1/10, Windows Server 2008/2008R/2012/2012R2
Mac OS environments	Macintosh OS X Native v10.7 or later
UNIX environments	UNIX Sun, Solaris UNIXSun , Solaris, HP-UX, SCO
	Open Server, RedHat Linux, IBM AIX
SAP environments	SAP R/3

SCANNER

Scanning Speed	ARDF: Max 80 originals per minute SPDF: Max 110 (simplex) 180 (duplex) originals per minute
Resolution	1200 dpi maximum
Original size	A3, A4, A5, B4, B5
Bundled drivers	Network TWAIN
Scan modes	E-mail, Folder

FAX

Circuit	PSTN, PBX
Compatibility	ITU-T (CCITT) G3
Transmission speed	G3: 2 seconds 200 x 100 dpi, JBIG 3 seconds 200 x 100 dpi, MMR 33.6 Kbps
Modem speed	33.6 Kbps
Resolution	Standard mode: 8 x 3.65 line per mm, 200 x 100 dpi, 8 x 7.7 line/mm, 200x 200 dpi Option mode: 8 x 15.4 line per mm, 400 x 400 dpi, 16 x 15.4 line/mm, 400 x 400 dpi
Compression method	MH, MR, MMR, JBIG

COPIER

Copying process	Dry Electrostatic Transfer System with Dual component Development 4 Drum method
Multiple copying	Up to 999 copies
Resolution	600 dpi / 4 bit
Zoom	From 25% to 400% in 1% steps

PAPER HANDLING

Recommended paper size	SRA3, A3, A4, A5, B4, B5, B6
Paper input capacity	Standard: 1200 sheets Maximum: 4700 sheets
Paper output capacity	Maximum: 1625 - 3625 sheets
Paper weight	52 - 300 g/m2

THINK COPIER CALL V COPIER

03 4280 2285 | 012 719 2285 | 017 627 2285

www.vcopier.com.my